

ONE SYSTEM TECHNICAL TIPS

- 1) ETCHING –
USE AN 80 TO 100 GRIT FILE TO ETCH. FIRST USE FILE TO GENTLY PUSH CUTICLE BACK OFF OF THE NAIL PLATE. WHILE ETCHING BE SURE TO REMOVE ALL REMNANTS OF SKIN LEFT ON NAIL PLATE NEAR CUTICLE AND SIDEWALLS.
- 2) DUSTING –
USE A NYLON MANICURING BRUSH TO DUST THE NATURAL NAIL. IT IS IMPORTANT THAT THE CUTICLES AND SIDEWALLS ARE COMPLETELY CLEAR OF ALL SKIN AND DUST.
- 3) **BALANCE – SPRAY OR BRUSH ON EACH NAIL 3 TIMES LET EACH COAT DRY COMPLETELY BEFORE APPLYING NEXT COAT.
- 4) APPLICATION – THE ONE SYSTEM NEEDS TO BE USED WETTER SO USE A LARGER BRUSH THAT WILL ALLOW YOU TO PICK UP A WETTER BALL. WHEN PLACED DOWN PRODUCT SHOULD FLOW NOT RUN. IF PRODUCT IS RUNNING THE ROOM MAY BE TOO COLD OR PRODUCT TOO WET. IF ROOM TOO COLD WARM LIQUID AND POWDER WITH OVERHEAD LIGHT WHILE ETCHING THE NAIL. IF PRODUCT TOO WET LIGHTLY TAP BRUSH ON PAPER TOWEL BEFORE PICKING UP BALL.
- 5) FILING – USE A 100 TO A 150 GRIT FILE MAKE SURE ACRYLIC IS COMPLETELY FLUSH WITH CUTICLE AREA AND SIDEWALLS.

****NOTE: ALTHOUGH THE ONE SYSTEM IS A
"VIRTUALLY" PRIMERLESS PRODUCT IN
SOME CASES IT WILL BE NECESSARY TO
USE PRIMER FOR MAXIMUM ADHESION.**

SALONS

GROUP

TM

Importers, Manufacturers and Distributors
to the Beauty and Nail Industries